




# **Screed flush duct systems**

## Information



## System overview

### Screed flush duct systems



# Screed flush duct systems

## Screed flush duct

### UEBS screed flush duct, 1 compartment

Screed-flush duct system consisting of 1x duct UEBS, 2x side panels UEBSMSP, respectively 1x tub UEBSMSW and 4x levelling units UEBSST.

article number	H <sub>min</sub> mm	N mm	B mm	L mm	E mm	t mm	P <sub>max</sub> kN	IP <sub>n</sub>	G kg
<b>S</b>									
<b>UEBS 20S</b>	60	+90	200	2000	400	1,5	2	IP 30	15,14

accessories included:

2 x <b>UEBSPT-3 AL</b>	carpet flange with hem 0/3 mm
1 x <b>UEBSE</b>	earthing connector
4 x <b>UEBSEA</b>	screed anchor
4 x <b>UEBSD 20S</b>	dummy cover

article number	H <sub>min</sub> mm	N mm	B mm	L mm	E mm	t mm	P <sub>max</sub> kN	IP <sub>n</sub>	G kg
<b>S</b>									
<b>UEBS 30S</b>	60	+90	300	2000	500	1,5	2	IP 30	20,30

accessories included:

2 x <b>UEBSPT-3 AL</b>	carpet flange with hem 0/3 mm
1 x <b>UEBSE</b>	earthing connector
4 x <b>UEBSEA</b>	screed anchor
4 x <b>UEBSD 30S</b>	dummy cover

article number	H <sub>min</sub> mm	N mm	B mm	L mm	E mm	t mm	P <sub>max</sub> kN	IP <sub>n</sub>	G kg
<b>S</b>									
<b>UEBS 40S</b>	60	+90	400	2000	600	1,5	2	IP 30	25,46

accessories included:

2 x <b>UEBSPT-3 AL</b>	carpet flange with hem 0/3 mm
1 x <b>UEBSE</b>	earthing connector
4 x <b>UEBSEA</b>	screed anchor
4 x <b>UEBSD 40S</b>	dummy cover


article number	H <sub>min</sub> mm	N mm	B mm	L mm	E mm	t mm	P <sub>max</sub> kN	IP <sub>n</sub>	G kg
<b>S</b>									
<b>UEBS 50S</b>	60	+90	500	2000	700	1,5	2	IP 30	30,86

accessories included:

2 x <b>UEBSPT-3 AL</b>	carpet flange with hem 0/3 mm
1 x <b>UEBSE</b>	earthing connector
4 x <b>UEBSEA</b>	screed anchor
4 x <b>UEBSD 50S</b>	dummy cover

accessories optional:

<b>UEBSMSP</b>	Plastic side panels
<b>UEBSQT S</b>	transverse cross bar
<b>UEBSMSP S</b>	Steel sheet side panels
<b>UEBSQT</b>	transverse cross bar
<b>UEBSMSW</b>	Floor tub
<b>UEBSST</b>	levelling support




# Screed flush duct systems

## Screed flush duct

### UEBSMSW Floor tub

article number	H <sub>min</sub> mm	N mm	B mm	L mm	G kg
<b>S</b>					
<b>UEBSMSW 60-20S</b>	60	+ 30	200	2000	4,28
<b>UEBSMSW 60-30S</b>	60	+ 30	300	2000	5,85
<b>UEBSMSW 60-40S</b>	60	+ 30	400	2000	7,42
<b>UEBSMSW 60-50S</b>	60	+ 30	500	2000	8,99
<b>UEBSMSW 80-20S</b>	80	+ 30	200	2000	4,91
<b>UEBSMSW 80-30S</b>	80	+ 30	300	2000	6,48
<b>UEBSMSW 80-40S</b>	80	+ 30	400	2000	8,05
<b>UEBSMSW 80-50S</b>	80	+ 30	500	2000	9,62
<b>UEBSMSW 100-20S</b>	100	+ 30	200	2000	5,54
<b>UEBSMSW 100-30S</b>	100	+ 30	300	2000	7,11
<b>UEBSMSW 100-40S</b>	100	+ 30	400	2000	8,68
<b>UEBSMSW 100-50S</b>	100	+ 30	500	2000	10,25
<b>UEBSMSW 120-20S</b>	120	+ 30	200	2000	6,17
<b>UEBSMSW 120-30S</b>	120	+ 30	300	2000	7,74
<b>UEBSMSW 120-40S</b>	120	+ 30	400	2000	9,31
<b>UEBSMSW 120-50S</b>	120	+ 30	500	2000	10,87




### UEBSMD 185V Assembly cover, quadrangular

article number	B mm	L mm	E1 mm	E2 mm	t mm	G kg
<b>S</b>						
<b>UEBSMD-185V 30S</b>	300	500	261	186	3	2,63
<b>UEBSMD-185V 40S</b>	400	500	261	186	3	3,92

accessories included:

2 x **BSS 4.8x16** Flat head tapping screw




### UEBSMD 260V Assembly cover, quadrangular

article number	B mm	L mm	E1 mm	E2 mm	t mm	G kg
<b>S</b>						
<b>UEBSMD-260V 40S</b>	400	500	261	261	3	2,63
<b>UEBSMD-260V 50S</b>	500	500	261	261	3	4,79

accessories included:

2 x **BSS 4.8x16** Flat head tapping screw




### UEBSBMD 260R Assembly cover, blank, round

article number	B mm	L mm	E mm	t mm	G kg
<b>S</b>					
<b>UEBSBMD-260R 40S</b>	400	500	260	3	5,23

accessories included:

2 x **BSS 4.8x16** Flat head tapping screw




# Screed flush duct systems

## Screed flush duct


### UEBSMSP Plastic side panels

article number	H1 mm	H2 mm	H <sub>min</sub> mm	N mm	L mm	G kg
<b>PA</b>						
<b>UEBSMSP 60</b>	48	68	60	+ 50	2000	1,00
<b>UEBSMSP 100</b>	88	108	100	+ 50	2000	1,02



### UEBSMSP S Steel sheet side panels

article number	H1 mm	H2 mm	H <sub>min</sub> mm	N mm	L mm	G kg
<b>S</b>						
<b>UEBSMSP 60S</b>	48	68	60	+ 50	2000	1,35
<b>UEBSMSP 100S</b>	88	108	100	+ 50	2000	1,29




### UEBSST levelling support

article number	H <sub>min</sub> mm	N mm	G kg
<b>S</b>			
<b>UEBSST 80S</b>	60	+ 50	0,18

accessories included:

- 2 x **LKS M5x10** Lens head screw
- 1 x **UBDSLFL 80** levelling support
- 1 x **UEBSV S** coupler



article number	H <sub>min</sub> mm	N mm	G kg
<b>S</b>			
<b>UEBSST 150S</b>	100	+ 50	0,20

accessories included:

- 2 x **LKS M5x10** Lens head screw
- 1 x **UBDSLFL 150** levelling support
- 1 x **UEBSV S** coupler

accessories optional:


- UGM SLF** Subsonic noise sleeve socket - levelling support

Impact noise behaviour | Screed-flush underfloor duct system

Technical information

Test

Duct UEBS and a outboard leveling



Test setup	$\Delta L_w$ (dB)	$L'_{n,w}$ (dB)
Duct system installed in floating screed, stimulation on screed and duct	28	53
Duct system installed in floating screed, stimulation on screed and duct with linoleum	33	48
Duct system installed in floating screed, stimulation on screed and duct with textile floor cover	40	41

Results according to test report 13-840 from March 2014


Test results

The test results with all proper applications show that the screed-flush underfloor system meets the standard noise protection requirement of 53 dB for floors in office buildings. The installation of the underfloor systems into the floating screed of a floor is therefore completely unproblematic as to the subsonic noise behaviour.

When laying carpet or linoleum floor covers, it is irrelevant in this context, whether the subsonic noise initiation occurs on screed or directly on the duct. Even in case of an initiation without floor cover the standard subsonic noise requirements are met.

A decoupling of the duct system with inside levelling through a rubber cuff renders a subsonic noise reduction of up to 1 dB. A complete decoupling by means of a subsequent removal of the levelling supports after the hardening of screed results in a subsonic noise reduction of up to 2 dB.

Duct UEBS and a internal leveling




Test setup	$\Delta L_w$ (dB)	$L'_{n,w}$ (dB)
Duct system installed in floating screed, stimulation on screed and duct without decoupling	28	53
Duct system installed in floating screed, stimulation on screed and duct, decoupling over the rubber sleeve	29	52
Duct system installed in floating screed, stimulation on screed and duct, decoupling suspended without leveling	30	51

Results according to test report 13-840 from March 2014


- Setup:
- 1. 50 mm cement screed
  - 2. 1 mm foil
  - 3. 20 mm impact sound insulation plate
  - 4. 40 mm heat insulation plate
  - 5. screed-flush duct UEBS
  - 6. 160 mm concrete slab
  - 7. floor cover (carpet 8,0 mm, linoleum 2,8 mm)

$L'_{n,w}$  = 81 dB stimulation on concrete slab  
 $L'_{n,w}$  = 50 dB stimulation on screed, without installations

Broadcasting room with carpet floor covers




Broadcasting room with linoleum floor covers






# Screed flush duct

## Assembly instruction




**Before mounting read the technical information „Assembly Requirements“.** Pre-assembled screed flush duct UEBS with four dummy covers in nominal widths  $B = 200, 300$  and  $400$  and  $500$  mm made of steel plate with a length  $L$  of  $2000$  mm. Optional levelling areas between  $60-110$  mm and  $100-150$  mm. Three systems are available. Steel plate side panel as the basic version, synthetic side panels for impact noise isolation and as a closed base tub for EMV cable routing.




### 1 | UEBS with steel plate side panel

Necessary mounting material in addition to the UEBS with steel plate side panel: 1x side panel set UEBSMSP S and 4x levelling units UEBSST.



### 2 | UEBS with synthetic side panel

Mounting material required in addition to the UEBS synthetic side panel: 1x panel set UEBSMSP, 4x levelling units UEBSST and 4x rubber cuffs UGM-SLF.




### 3 | UEBS with tub

Mounting material needed in addition to UEBS with steel plate tub: 1x base tub UEBSMSW and 4x levelling units UEBSST.




### 4 | Duct alignment

Measure the duct course according to the approved layout drawing and mark it using a plumb line. Lay out pre-assembled duct according to duct course and marking. Note binding height metre point.



### 5 | Levelling units / side plate

Insert and pre-position one side panel and two levelling units per duct side sideways into the duct aluminium profile. The individual levelling units can be roughly set to the required height in advance.




### 6 | Duct piece assembly

Release end dummy cover of the delivered duct, align ducts and finally push together. Link levelling units and cross beams to the duct parts. Note that the cross beam is tightly screwed to the dummy cover as provided by the factory.


# Screed flush duct

## Assembly instruction



### 7 | Positioning the levelling units

Position levelling units according to the course of the duct at intervals of one metre and screw them to the aluminium profile. Comply with the levelling unit height of 80 respectively 150 mm. Firmly connect together all metal parts of the duct system.




### 8 | Mounting the duct

Screw levelling units so that they overlap with both duct pieces. While doing so, comply with that the dummy cover is tightly connected with the closest following duct part by means of a cross beam.



### 9 | Plugging of the levelling foot

Align leveling on the side wall and drill a hole. Fasten levelling feet firmly to the rough concrete using nail plugs.



### 10 | Adjusting the levelling

Level the completely mounted duct system to the required screed height using a laser or digital tube level. The levelled duct system must not be walked upon or strained in any other way.



### 11 | Mounting the separating panels

Plug the synthetic separating panels directly into the rough concrete in 1-metre-intervals.



### 12 | Screed anchor

Latch screed anchor into the duct segment's outer profile. The screed anchors serve as a firm connection between duct and screed, thereby helping to prevent a later fissuring. Four screed anchors per duct unit are included in the delivery.




### 13 | Shortening the levelling units

If needed the levelling units can be shortened below screed level. All open areas must be masked according to DIN before the application of screed.



### 14 | Low levelling of 60-100mm

For a floor construction of up to 110 mm, use levelling unit UBSST 80S. The side panel brackets must be turned according to the desired side height. Correspondingly, a levelling height of 60-90 mm respectively of 80-110 mm is possible.




### 15 | High levelling of 100-150mm

For a floor construction of up to 150 mm, use levelling unit UBSST 150S. The side panel brackets must be turned according to the desired side height. Correspondingly, a levelling height of 100-130 mm respectively of 120-150 mm is possible.



# Screed flush duct

## Assembly instruction




### 16 | Impact sound decoupling

For an impact sound decoupling of the duct system use synthetic side panels only. Additionally push rubber cuffs over the levelling units. Then mount the two connected components onto the rough concrete using nail plugs.




### 17 | Tube mounting

When using a floor tube, the required levelling height must be complied with. Select tube type H = 60, 80, 100 respectively 120 mm and push into the duct side profile. The levelling is done after the plugging to the rough concrete.




### 18 | Assembly covers

After the assembly of the duct system, the corresponding dummy covers must be replaced by assembly covers for installation units and adjusted to the duct course. To mount installation units, use special claws UDKSEB with a clamping range of at least 2 mm.



### 19 | Cross beam

In the course of adjusting the cover sections, the cross beam must be loosened from the dummy cover or assembly cover. The corresponding cover must be shortened, drilled in again and finally screwed into the side profile.



### 20 | Cross beam B = 500 mm

The 500 mm duct covers have additional cross beams. The cross beams are attached with a distance of 25 cm from one another. An additional duct support is therefore unnecessary.




### 21 | Carpet edge

According to delivery condition, the turnable carpet protection edge is flush with the duct embedded in the screed-flush duct. If needed, it can be turned creating a 3 mm floor cover edge.



### 22 | Dummy cover

The dummy covers (width B - 6 mm) are delivered with one cross beam that can be screwed on one side, and are to be bolted to the side profile of the duct in offset on the nearest overlapping cross beam with two bolts.



### 23 | End piece

Insert the end piece sideways into the duct profile and screw tightly together. A height adjustment by 3 mm is possible by means of carpet protection edge. If needed, the lower openings can be masked.




### 24 | Accessory set for 75 mm height

Notch and burr the side panel of the duct. Bend open side panel of the hollow space floor box along the perforation and insert one mounting sleeve UM between duct and hollow space floor box. Fix hollow space floor box to the rough concrete and insert shuttering unit.


# Screed flush duct

## Assembly instruction




### 25 | Accessory set for 60-110 mm height

Notch and burr the side panel of the duct. Connect accessory set to the duct using a coupler and affix to the rough concrete. The installation unit can be inserted immediately after the completion of the screed work and the removal of the dummy cover.




### 26 | Corner connection

The synthetic corner connection ( $b = 26 \text{ mm}$ ) is for making a formed part during assembly. After cutting the duct profile, insert the connection into it and screw them together using the steel plate corner connection. Depending on the rotating direction the corner connection can be used as an inside or outside corner.




### 27 | Coupler plate

A coupler plate must be inserted in addition to the corner connection. The plate should be mounted in the corner using the provided screws, thus creating the necessary fastening point.




### 28 | Cutting a 90° bend

In order to create a 90° bend, an aluminium outside profile must be shortened by 28 mm and both aluminium inside profiles by B - 22 mm each, after the laying of the duct. Side panels and dummy covers should be cut as needed.




### 29 | Mounting a 90° bend

Push duct pieces together and link together using the separately supplied bend assembly set. Then screw them together using the corner connection.




### 30 | 90° bend final assembly

Cut cover sections and if needed, ream mounting holes. Insert cross beam for support. Slide in carpet edge, 3 mm overlaying in the corners, and mark open areas. Cover and screw duct section.




### 31 | Cutting a T-junction

In order to create a T-junction after the laying of the duct, the duct must be notched end-to-end on one side by B + 6 mm. Shorten the aluminium profiles of the incoming duct on both sides by 6 mm each. Cut side panels and dummy covers.



### 32 | Mounting a T-junction

Push duct pieces together and link together using the T-junction assembly set included in the delivery. Then screw them together using the corner connection. In order to create an intersection, use two T-junction assembly sets.



### 33 | T-junction final assembly

Cut cover, ream mounting holes and insert cross beam for support. Slide in carpet edge, making sure that they are overlaying 3 mm in the corners and mark open areas. Cover and screw duct section. Do not lay dummy cover joints in junction areas.



# Screed flush duct

## Assembly instruction



**34 | Dummy cover segment**  
Cut the cover segment (L < 500 mm) to the required length.



**35 | Dummy cover segment**  
Create additional drill holes with reduction for countersunk head screws.




**36 | Dummy cover segment**  
Fasten the dummy cover segment with additional countersunk head screw with the side profile.




**37 | UEBS Duct system for wet-maintenance linoleum covers**  
First, completely remove the rubber insert (UEBSPGD) from the side profile of the duct.




**38 | UEBS Duct system for wet-maintenance linoleum covers**  
Next, glue the rubber seal (UGDB15-R300 1.8) onto the side profile in longitudinal direction, covering the entire area of the duct.




**39 | UEBS Duct system for wet-maintenance linoleum covers**  
In addition, glue the transverse cross bar (UEBSQT) and the end piece (UEBSES) flush to the rubber seal.



**38 | Sealing of the duct system**  
Finally, seal all open areas of the duct system as well as the assembly sets using silicone.



**41 | Transverse cross bar**  
If there is an increased load, an additional transverse cross bar must be inserted centrally under the dummy cover.



**40 | Screed work**  
Pay attention to a good screed compaction and conciseness in order to avoid cracks in the screed. Apply screed directly to the aluminum profile of the channel. Don't use insulation strips for decoupling.



Errors and technical modification subject to change. Reproduction as well as electronic duplication only with our written permission. With appearance of this print all preceding documents lose their validity.

